

## Shrink sleeve - WMS 4,8 (60X9)RXL YE - 0803103

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Shrink sleeve, Roll, yellow, unlabeled, can be labeled with: THERMOMARK W, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK X1.2, Perforated, Lettering field: 60 x 9 mm



The illustration shows WMS 6,4 (30X10)R

### Why buy this product

- WMS ... shrink sleeves provide permanent and captive conductor and cable marking
- The sleeves are pre-assembled for optimum use of material
- The conductor to be marked is simply threaded through the sleeve and fixed by shrinking the sleeve
- The sleeves remain flexible after shrinking
- Up to four markers per sleeve are separated by perforations
- UL 224 (125°C, 600 V, all tubing)
- CSA.C22.2 No. 198.1 (125°C, 600 V, all tubing)

### Key Commercial Data

|                                      |          |
|--------------------------------------|----------|
| Packing unit                         | 1 STK    |
| Weight per Piece (excluding packing) | 1100.0 g |
| Custom tariff number                 | 39173200 |
| Country of origin                    | China    |

### Technical data

#### Dimensions

|                |        |
|----------------|--------|
| Length (b)     | 60 mm  |
| Width (a)      | 9 mm   |
| Cable diameter | 4.8 mm |

#### General

|                       |              |
|-----------------------|--------------|
| Color                 | yellow       |
| Base element material | polyolefine  |
| Components            | Halogen-free |
| Material              | Polyolefine  |

# Shrink sleeve - WMS 4,8 (60X9)RXL YE - 0803103

## Technical data

### General

|                             |                             |
|-----------------------------|-----------------------------|
| Wipe resistance             | DIN EN 61010-1 (VDE 0411-1) |
| Number of individual labels | 2500                        |

### Standards and Regulations

|                 |                             |
|-----------------|-----------------------------|
| Wipe resistance | DIN EN 61010-1 (VDE 0411-1) |
|-----------------|-----------------------------|

## Classifications

### eCl@ss

|            |          |
|------------|----------|
| eCl@ss 4.1 | 24190219 |
| eCl@ss 5.1 | 27400401 |
| eCl@ss 6.0 | 27400401 |
| eCl@ss 8.0 | 27400105 |
| eCl@ss 9.0 | 27400401 |

### ETIM

|          |          |
|----------|----------|
| ETIM 4.0 | EC000217 |
| ETIM 5.0 | EC000217 |

## Accessories

### Accessories

#### Ink ribbon

Ink ribbon - THERMOMARK-RIBBON 64-WMSU - 0801360



Ink ribbon, specifically for WMS... shrink sleeves, length: 300 m, width: 64 mm, color: black

Ink ribbon - THERMOMARK-RIBBON 110-WMSU - 0801358



Ink ribbon, specifically for WMS... shrink sleeves, length: 300 m, width: 110 mm, color: black

### Printing system accessories

## Shrink sleeve - WMS 4,8 (60X9)RXL YE - 0803103

### Accessories

Media hub - THERMOMARK ROLL-ERH - 5146448



External media hub, for the THERMOMARK ROLL, for roll diameter of 150 to 400 mm