



Features

- Level B EMI filter
- Fully regulated output
- High efficiency
- Weight = 0.35 lbs.
- 5 year warranty

Environmental

- Operating temperature0°C to 40°C
- Storage temperature-55°C to 85°C

EMI

Meets FCC class B, CISPR 22 class B

Safety

UL/cUL UL-60950

Electrical specifications

Input

- Voltage..... 100-120 VAC
- Current0.25 Amp @ 115 VAC
- Frequency50-60 Hz
- Input connector 2pin NEMA 5/15 (no Ground pin)

Output

- Hold up time20ms minimum at full load, 115 VAC
- Over voltage protection..Built-in
- Line regulation.....TYP +/- 1%
- Load regulation.....TYP +/- 5%
- Set point..... +/- 3% at 60% load
- Transient responseRecovery within 1% of nominal output within 2ms for 50% to 100% load change. Max excursion of 6% from set point
- Over current protection .. 150% of maximum load
- Short circuit protection ..Pulsing mode, auto recovery
- Efficiency..... 75% minimum at full load and 115 VAC
- Ripple/noise (V_{p-p}) +/- 1% (20 MHz bandwidth)
- Output connector Barrel connector (5.5 x 2.5 x 9.5mm)



Output Electrical Specifications

Model No.	Voltage	Power	Current
WM1005-760	5V	10W	2A
WM1012-760	12V	10W	0.8A
WM1024-760	24V	10W	0.4A



ELPAC Power Systems, 1562 Reynolds Ave, Irvine CA 92614
 Phone (949) 476-6070 Fax (949) 476-6075 Toll free # (888) ELPAC-80
 E-mail: sales@elpac.com or engr@elpac.com