



NOTES:

1. METALSHELLS: COPPER ALLOY;
min. 315µin TIN over 40-80µin NICKEL
2. INSULATOR: TPE
3. CLAMPS: STAINLESS STEEL
4. SCREW: STAINLESS STEEL
5. CONNECTOR IS PART MARKED: PART NO. CONEC ABC

Directive 2002/95/EC RoHS compliant

No. of pos.	A _{-0,76}	B _{+0,25}	C	Part-No. Bulk package	Part-No. Single package
9	31,19	16,46	25,00 ^{+0,12} _{-0,13}	165X16669X	165X16669XE
15	39,52	24,79	33,30 ^{+0,15} _{-0,1}	165X16679X	165X16679XE
25	53,42	38,50	47,04 ± 0,13	165X16689X	165X16689XE
37	69,70	54,96	63,50 ± 0,13	165X16699X	165X16699XE
50	67,31	52,55	61,10 ^{+0,14} _{-0,11}	165X16709X	165X16709XE

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH

DO NOT ALTER CAD DRAWING BY HAND

				tolerance		scale: 2:1
					dim. in mm	material: SEE NOTES
				date	name	title: HOOD 9 - 50pos. FOR PLUG CONNECTOR water resiatant, shielded for EMI/RFI
				drawn 30.06.11	Henneboel	
				appd. 01.07.11	Fischer	
				norm		
				d-old		dwg no: 16K1A2842
a	Original			CONEC ®		DIN-A4
rev.	description	date	name			sh: 1
						part no: SEE TABLE

