



WSW order code: DK-2633-xx

Cable length:

- 01: 1000+50/-0      07: 7000+100/-0
- 02: 2000+100/-0    10: 10000+100/-0
- 03: 3000+100/-0    15: 15000+150/-0
- 05: 5000+100/-0

- Performance:
- a. Insertion Loss: <0.3dB
  - b. Return Loss: >20dB
  - c. Fiber Extension: -100nm,H,+100nm
  - d. Ferrule End-Face Radius:  $7 < R < 25$ mm
  - e. Aper Offset:  $\leq 50$ um
  - f. Increase in insertion Loss after 500 mating: 0.2 dB max
  - g. Operation Temperature: -40°C to +70°C
  - h. Storage Temperature: -40°C to +85°C
  - i. The bend radius must respect a minimum of 30mm
  - Ⓜ j. Mating cycle: 500times

**RoHS compliant**

Unit: mm

No.	Specifications	Qty.
①	Ø3.0mm Duplex, MM62.5/125 Duplex cable / POE LSZH/orange	1
②	3.0mm LC/PC MM Connector/Beige	4
③	LC Duplex Clip/Beige	2
④	LC 3.0mm Boot/Beige	4
⑤	Tail Identification Marker (3mm C-Clip)/NO.A2.A1:B2:B1	4
⑥	LC Heatshrink Tube/Black	2

Scale	Free			Date	Name	Customer-No.		
TOLERANCE				22.06.2016	Amy	ASSMANN WSW-No.	DK-2633-xx	
				09.02.2018	Amy			
		②	Update					
DIM	TOL	①	Change the specification	22.01.2018	Tom	Drawing-No.	ASS 7672 CA	rev01
		①	Drawn	22.06.2016	Amy	Replace		Sheet
Angle	TOL							

**ASSMANN**  
WSW components

1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	A