



POS.	A ^{-0.76}	B ^{-0.25}	C	PART NO.
9	31.19	16.46	25.00 ^{+0.12} _{-0.13}	242A15030X
15	39.52	24.79	33.30 ^{+0.15} _{-0.1}	242A15040X
25	53.42	38.50	47.04 ^{+0.13}	242A15050X
37	69.70	54.96	63.50 ^{+0.13}	242A15060X

NOTES:

- METALSHELLS: STEEL; TIN PLATED
- INSULATOR: PBTP GF UL 94 V-0
- CONTACTS: COPPER ALLOY
- PLATING: HARD GOLD OVER NICKEL
- PCB-SNAP: COPPER ALLOY; TIN PLATED
PCB HOLE ϕ 3.1 \pm 0.1; PCB THICKNESS $t=$ 1.6mm
- CAPACITANCE: 1300pF \pm 20%
- DIELECTRIC WITHSTANDING VOLTAGE: 424VDC
- MAXIMUM TORQUE VALUE FOR THREAD: 6" LBS
- = CRITICAL DIMENSION: SPC

used for: D-SUB FILTER

DO NOT ALTER CAD DRAWING BY HAND
 OWNERSHIP AND COPYRIGHT OF CONEC GMBH
 WRITTEN PERMISSION
 BE PASSED ON TO A THIRD PARTY WITHOUT
 REPRODUCED IN ANY WAY, AND MAY NOT

CONEC CORPORATION BRAMPTON, ONTARIO		tolerance	2:1 (5:1)
1998		material	SEE NOTES
drawn	08.05.	Barcinski	
appd.	08.05.	Mickenbecker	
norm	DIN 41652		
d-old			
name		title	
D		D-FILTER FEMALE P-TYP	
9-37pos. PIN 5.8mm		WITH THREADED SPACER CLIP	
dwg no:		[CAD/ REL.13]	DIN-A
24K11Y8A			3
product no:		SEE TABLE	sh: 1/1

THIS DRAWING MAY NOT BE COPIED OR
 REPRODUCED IN ANY WAY, AND MAY NOT
 BE PASSED ON TO A THIRD PARTY WITHOUT
 WRITTEN PERMISSION
 OWNERSHIP AND COPYRIGHT OF CONEC GMBH
 DO NOT ALTER CAD DRAWING BY HAND

rev.	description	date	name

CONEC®