



Part Number: 8669

Shielding & Bonding, 8.9 AWG (336x34) Braided TC

[Request Sample](#)

Product Description

8.9 AWG stranded (336x34) braided tinned copper conductor.

Technical Specifications

Physical Characteristics (Overall)

Conductor

AWG	Stranding	Material
8.9	336x34	Braided TC - Braided Tinned Copper

Conductor Count:	1
Conductor Size:	8.9 AWG

Insulation

Material
N/A

Outer Jacket Material

Material
No Jacket

Construction and Dimensions

Braided Tubular I.D.1:	0.5 in
Circular Mil Area (CMA)1:	13300

Electrical Characteristics

Conductor DCR

Nominal Conductor DCR	
0.78 Ohm/1000ft	
Shielding:	Braid(s)

Current

Max. Recommended Current [A]
62.0 A

Mechanical Characteristics

Bulk Cable Weight:	45.6 lbs/1000ft
--------------------	-----------------

Standards

UL AWM Style:	N/A
Military Specification:	N/A

Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (ROHS II):	Yes
EU Directive 2012/19/EU (WEEE):	Yes

EU Directive 2015/863/EU:	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
EU RoHS Compliance Date (yyyy-mm-dd):	2004-01-01
CA Prop 65 (CJ for Wire & Cable):	Yes
MII Order #39 (China RoHS):	Yes

Flammability, LS0H, Toxicity Testing

UL voltage rating:	N/A
--------------------	-----

Plenum/Non-Plenum

Plenum (Y/N):	No
---------------	----

Part Number

Variants

Item #	Color	Footnote
8669 000250	None	C E
8669 00050	None	

Footnote:	C - CRATE REEL PUT-UP.
Footnote:	E - MAY CONTAIN MORE THAN 1 PIECE. MINIMUM LENGTH OF ANY ONE PIECE IS 25'.

© 2018 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.