



▲ **CIRCUIT: 4PDT**
CONTACT CONFIGURATION

▲ SWITCH FUNCTION	POS. 1	POS. 2	POS. 3
	DN	DN	DN
	DN	DN	DN
	DN	DN	DN
	DN	DN	DN
	DN	DN	DN
	DN	DN	DN
	DN	DN	DN
	DN	DN	DN
	DN	DN	DN
	DN	DN	DN
	DN	DN	DN

NOTES:

1. ALL DIMENSIONS IN MM [INCH]
2. GENERAL TOLERANCE: X.XX=±0.4 X.XXX=±0.25
3. TERM. NOS. FOR REF. ONLY
4. RATING: 5A@ 120VAC OR 28VDC 2A@ 250VAC
5. ELECTRICAL LIFE: 40,000 CYCLES AT FULL LOAD
6. INSULATION RESISTANCE: 1000M OHMS MIN.
7. DIELECTRIC STRENGTH: 1000V RMS
8. OPERATING TEMP: -30C TO + 85C
9. 2002/95/EC (ROHS) COMPLIANT
10. HARDWARE TO BE SHIPPED BULK:
 T100011 - LOCK WASHER, QTY 1
 T100015 - LOCK RING, QTY 1
 T100000 - HEX NUT, QTY 2



1004P1T6B1M1QE H

B	16565	11.43 TO 12.30 CORRECTION	10/23/06	TN
A	16096	RELEASED FOR PRODUCTION	6/5/06	CT
REV.	ECN NO.	DESCRIPTION	DATE	CHKD

SCALE	TITLE	DATE	DR	DWG	REV
NONE	1004P1T6B1M1QE H	6/5/06	CT	ST141009	B

THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED